

Pergotenda®
100



The only wood Pergotenda® that is modular and can be freestanding or wall mounted, pitched or flat, as well as linked with other Pergotenda® 100s, making it easy to cover large spaces.

Time to grow



Pergotenda® 100 with Clear Vinyl Window Stratus Screens | Princi Italia, Plano TX

PERGOTENDA® 100



Pergotenda® 100 is a modular freestanding or wall mounted retractable covering system custom made to protect against sun and rain. It consists of a glulam wood structure and a folding canvas. The fabric is supported by intermediate tubes (1.6"x2") and terminals (3.2"x2") set parallel approximately every 20". It slides on guides (2" x 3.6") with patented sliders that have 6 asymmetrical wheels with a maximum capacity of 1000 lbs each. The toothed drive belt inserted in each guide, with strands that are completely covered to resist even in saline environments, is driven by a pulley and a single transmission shaft to guarantee the uniform movement of the canvas. The breaking drive load of each belt is 2,000 lbs. The PT100 system is operated by a radio-controlled Dunker D839 motor. The structure, in autoclave treated Scandinavian pine wood (class 3 - UNI EN 335-3), is available in 4.7"x4.7" section, with added possibility of choosing different structure and board. Hardware and accessories are 304 stainless steel. While Corradi USA possesses a great deal of data related to engineering for the Pergotenda® product line that is related to wind ratings and load data that has been developed through specific product tests, case studies and IBC testing. It is understood that when required and due to the custom nature of our projects, engineering must be project specific and adhere to the rules and regulations at the local level where such a project shall be planned and installed.


FRAME COLORS

WOOD STAIN*

Scandinavian laminar pine wood used for wood Pergotenda® is structurally composed of layers glued together with adhesives that resist humidity. Pressure treated with mineral salts in an autoclave significantly increasing resistance to biological degradation. The support tubes come in: White Quartz, Glacier, & Beach Sand to match with the Eclissi fabric.



CHESTNUT



WALNUT



ANTHRACITE




WHITE

*CUSTOM COLOR PAINTING IS ALSO AVAILABLE
Due to print variation these finish images should not be used for final production specifications.

FABRICS

ECLISSI BLACKOUT FABRIC

Eclissi fabric is exclusively used by Corradi USA for Pergotenda® structures. It is a High tenacity 1100 Dtex Polyester base fabric with PVC laminate. The embossed finish on the inner side gives a textile appearance and a dynamic weft effect on the viewable surface. The outer side has an anti-dust acrylic lacquer. This unique 4-ply material has a blackout layer that also acts as a radiant barrier, providing superior heat resistance and heat gain as compared to other textiles used in these types of applications. It is available in 3 colors:



ECLISSI WHITE



ECLISSI GREY



ECLISSI IVORY

OTHER RETRACTABLE ROOF FABRICS AVAILABLE

SERGE FERRARI SOLTIS PROOF W96

See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS PROOF 502

See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS PERFORM 92



See Fabrics section pg. 155 for more information on this fabric.

SERGE FERRARI SOLTIS HORIZON 86

See Fabrics section pg. 155 for more information on this fabric.

MOTORS

RADIO CONTROLLED DUNKER D839



PITCHED MAX DIMENSIONS
(1 MODULE)

	Width	Projection
2 runner	138"	276"
3 runner	276"	276"
4 runner	413"	276"

FLAT MAX DIMENSIONS
(1 MODULE)

	Width	Projection
2 runner	138"	236"
3 runner	276"	236"
4 runner	413"	236"

*Note: when pitched and has 4 runners, system will require 2 motors. 5 runner is not available with the PT100 whether pitched or flat.

FLAT MAX DIMENSIONS TRAPEZOIDAL slack		
	Width	Projection
2 runner	138"	236"
3 runner	276"	236"
4 runner	472"	236"

Cultivate and flourish



Pergotenda® 100 | Outdoor Living Solutions, London ON Canada

FEATURES

ANTIDRIP SYSTEM Weldable PVC profile on the upper part of the canvas for lateral rainwater retention. This PVC profile is welded to each far side of a pitched roof canopy to prevent water from dripping over the sides and forces the water to shed into the gutter system.

ANTISPRAY PROFILE PVC profile inserted on the lateral side of the runner for retention of rainwater spray. Always in addition to the ANTIDRIP SYSTEM. The AntiSpray prevents water from a heavy downpour from "splashing" over the AntiDrip profile and dripping over the sides.

MODULAR System modules can be connected for exponentially greater coverage.

MOTORIZATION All Pergotenda® are motorized, giving you complete control at the touch of a button.

HOOD The Protective Hood Cover is an aluminum corrugated standing seam cover that is positioned where the unit mounts to the wall or at the back of the unit on a Freestanding model for the purpose of protecting the Roof Canopy Swags that are created when the roof retracts and to prevent any water or debris from collecting in the swags. The Protective Hood Cover is powder coated for longevity.

OPTIONS

ADD-ON INTERMEDIATE SUPPORT TUBE Used to reduce the height of the canopy swag when the roof unit is retracted, usually for purposes of clearing a door opening or a window. Only two (2) tubes total may be added to any single roof canopy.

ADD-ON RUNNER The mechanical Runner is the equivalent of roof truss or rafter and is what the roof canopy is attached to. Adding a Runner is considered when the roof pitch angle needs to be reduced to properly shed water and manage it into the gutter systems. Adding a runner may also be considered to reduce the pitch of the roof for design purposes as well.

FAUX CEILING A unique option that hangs a colorful fabric beneath the roofing material to add warmth and atmosphere to the room. The Faux Ceiling fabric can provide for an excellent opportunity to blend other colors or materials that are part of furnishings or cushions. The softer fabric material may also be a benefit in reducing noise or providing other minimal acoustic properties to dampen surrounding noise. This option will depend on the type of fabric. The Faux Ceiling fabric generally must be from the Corradi USA collection or an approved alternate.

FIXED GUTTER (pitched versions only) Extruded aluminum profile for rainwater collection fixed to the end support tube. Down pipes and accessories included.

LIGHTING The Pergotenda® lighting system is a custom designed system that seamlessly integrates into the Pergotenda® intermediate tubes.

PITCHED OR FLAT Both pitched (angled) roof and flat roof options are available for the Impact.

STRATUS SCREEN An exterior screen specifically designed to integrate into most Pergotenda® systems for complete enclosure that assists in protection from the elements and gives the option of privacy.

TRAPEZOIDAL FABRIC (flat versions only) An alternative drainage option for flat systems to let you control which side of the system you want rain to fall off.

UNDERSIDE DRIP-COLLECTION RIM (flat versions only) Welded PVC profile on the underside of the roof canopy to channel water into the side gutters and to prevent water from running along the underside of the roof canopy and dripping down.

FREESTANDING OR WALL MOUNT Can be attached to wall or self supporting.